

F-II Series Vacuum Generator



Shown with fittings installed

This generator is long, sleek and very efficient. The straight-thru design produces impressive flows for a single stage device. The large screw-on exhaust silencer provides convenient access for cleaning thus assuring reliability and long service life in demanding applications. The large 3/8npt ports are perfect for high flow action!

F-II Series Vacuum Generator Specifications

| | |
|----------|----------------|
| Diameter | 1.25 in. |
| Length | 9.0 in. |
| Ports | 3/8" npt (all) |
| Material | Acetal Black |

F-II Series Vacuum Generator Models

| Part# | Air Consumption | Vacuum Level @ 65psi (5 BAR) |
|-------|-----------------|------------------------------|
| F2M05 | 2.6 scfm | 20 in-Hg |
| F2H05 | 2.6 scfm | 27 in-Hg |
| F2M06 | 3.6 scfm | 20 in-Hg |
| F2H06 | 3.6 scfm | 27 in-Hg |
| F2M07 | 4.9 scfm | 20 in-Hg |
| F2H07 | 4.9 scfm | 27 in-Hg |
| F2M08 | 6.8 scfm | 20 in-Hg |
| F2H08 | 6.8 scfm | 27 in-Hg |
| F2M09 | 8.2 scfm | 20 in-Hg |
| F2H09 | 8.2 scfm | 27 in-Hg |